


## Technical Data Sheet

### Right Angle Lens Chip LEDs with Bi-Color (Multi-Color)

**17-223/BHR7C-C30/3C**

#### Features

- Package in 8mm tape on 7" diameter reel.
- Compatible with automatic placement equipment.
- Compatible with infrared and vapor phase reflow solder process.
- Multi-color type.
- Pb-free.
- The product itself will remain within RoHS compliant version.



#### Descriptions

- The 17-223 SMD LED is much smaller than lead frame type components, thus enable smaller board size, higher packing density, reduced storage space and finally smaller equipment to be obtained.
- Besides, lightweight makes them ideal for miniature applications. etc.




#### Applications

- Backlighting in dashboard and switch.
- Telecommunication: indicator and backlighting in telephone and fax.
- Flat backlight for LCD, switch and symbol.
- General use.



#### Device Selection Guide

Chip		Emitted Color	Resin Color
Type	Material		
BH	InGaN	Blue	Water Clear
R7	AlGaInP	Dark-Red	

**Package Outline Dimensions**



For reflow soldering (propose)



**Note:** The tolerances unless mentioned is  $\pm 0.1\text{mm}$ , Unit = mm

**Absolute Maximum Ratings (Ta=25°C)**

Parameter	Symbol	Rating	Unit
Reverse Voltage	V <sub>R</sub>	5	V
Forward Current	I <sub>F</sub>	BH:25 R7:25	mA
Peak Forward Current (Duty 1/10 @1KHz)	I <sub>FP</sub>	BH:100 R7:60	mA
Power Dissipation	P <sub>d</sub>	BH:95 R7:60	mW
Electrostatic Discharge (HBM)	ESD	BH:150 R7:2000	V
Operating Temperature	T <sub>opr</sub>	-40 ~ +85	°C
Storage Temperature	T <sub>stg</sub>	-40 ~ +90	°C
Soldering Temperature	T <sub>sol</sub>	Reflow Soldering : 260 °C for 10 sec. Hand Soldering : 350 °C for 3 sec.	

**Electro-Optical Characteristics (Ta=25°C)**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition	
Luminous Intensity	BH	22.5	-----	57.0	mcd	If=5mA	
	Iv						
Viewing Angle	R7	14.5	-----	36.0	2θ 1/2		deg
Peak Wavelength	BH		468		λ p		nm
	R7		639				
Dominant Wavelength	BH	465.0	-----	475.0	λ d		nm
	R7	621.5	-----	633.5			
Spectrum Radiation Bandwidth	BH		25		Δ λ		nm
	R7		20				
Forward Voltage	BH	2.7	-----	3.2	VF	V	
	R7	1.55	-----	2.15			
Reverse Current	BH			50	IR	μ A	
	R7			10			

**Notes:**

1. Tolerance of Luminous Intensity ±11%
2. Tolerance of Dominant Wavelength ±1nm
3. Tolerance of Forward Voltage ±0.05V

**Bin Range Of Luminous Intensity**

**BH**

Bin	Min	Max	Unit	Condition
1	22.5	36.0	mcd	I <sub>F</sub> =5mA
2	36.0	57.0		

**R7**

Bin	Min	Max	Unit	Condition
1	14.5	22.5	mcd	I <sub>F</sub> =5mA
2	22.5	36.0		

**Bin Range Of Forward Voltage**

**BH**

Bin	Min	Max	Unit	Condition
1	2.70	2.80	V	I <sub>F</sub> =5mA
2	2.80	2.90		
3	2.90	3.00		
4	3.00	3.10		
5	3.10	3.20		

**R7**

Bin	Min	Max	Unit	Condition
1	1.55	1.75	V	I <sub>F</sub> =5mA
2	1.75	1.95		
3	1.95	2.15		

**Bin Range Of Dom. Wavelength**

**BH**

Groups	Bin	Min	Max	Unit	Condition
Z	X	465.0	470.0	nm	I <sub>F</sub> =5mA
	Y	470.0	475.0		







**R7**

Groups	Bin	Min	Max	Unit	Condition
B	E5	621.5	625.5	nm	I <sub>F</sub> =5mA
	E6	625.5	629.5		
	E7	629.5	633.5		







**Notes:**

- 1.Tolerance of Luminous Intensity  $\pm 11\%$**
- 2.Tolerance of Dominant Wavelength  $\pm 1\text{nm}$**
- 3.Tolerance of Forward Voltage  $\pm 0.05\text{V}$**

**Typical Electro-Optical Characteristics Curves**  
**BH**



**Typical Electro-Optical Characteristics Curves**  
**R7**





**17-223/BHR7C-C30/3C**

**Label explanation**


**CAT: Luminous Intensity Rank**

**HUE: Dom. Wavelength Rank**

**REF: Forward Voltage Rank**




**Reel Dimensions**




**Note:** The tolerance unless mentioned is  $\pm 0.1$ mm, unit is mm.

**Carrier Tape Dimensions: Loaded quantity 3000 PCS per reel**



**Note:** The tolerances unless mentioned is  $\pm 0.1$ mm ,Unit = mm

**Moisture Resistant Packaging**



**Reliability Test Items And Conditions**

The reliability of products shall be satisfied with items listed below.

Confidence level : 90%

LTPD : 10%

No.	Items	Test Condition	Test Hours/Cycles	Sample Size	Ac/Re
1	Reflow Soldering	Temp. : 260°C±5°C Min. 5sec.	6 Min.	22 PCS.	0/1
2	Temperature Cycle	H : +100°C 15min ∫ 5 min L : -40°C 15min	300 Cycles	22 PCS.	0/1
3	Thermal Shock	H : +100°C 5min ∫ 10 sec L : -10°C 5min	300 Cycles	22 PCS.	0/1
4	High Temperature Storage	Temp. : 100°C	1000 Hrs.	22 PCS.	0/1
5	Low Temperature Storage	Temp. : -40°C	1000 Hrs.	22 PCS.	0/1
6	DC Operating Life	IF = 20 mA	1000 Hrs.	22 PCS.	0/1
7	High Temperature / High Humidity	85°C / 85%RH	1000 Hrs.	22 PCS.	0/1

**Precautions For Use**

1. Over-current-proof

Customer must apply resistors for protection, otherwise slight voltage shift will cause big current change ( Burn out will happen ).

2. Storage

2.1 Do not open moisture proof bag before the products are ready to use.

2.2 Before opening the package: The LEDs should be kept at 30°C or less and 90%RH or less.

2.3 After opening the package: The LED's floor life is 1 year under 30°C or less and 60% RH or less.


If unused LEDs remain, it should be stored in moisture proof packages.

2.4 If the moisture absorbent material (silica gel) has faded away or the LEDs have exceeded the storage time, baking treatment should be performed using the following conditions.

Baking treatment : 60±5°C for 24 hours.

3. Soldering Condition

3.1 Pb-free solder temperature profile



3.2 Reflow soldering should not be done more than two times.

3.3 When soldering, do not put stress on the LEDs during heating.

3.4 After soldering, do not warp the circuit board.


**17-223/BHR7C-C30/3C**

**4.Soldering Iron**

Each terminal is to go to the tip of soldering iron temperature less than 350°C for 3 seconds within once in less than the soldering iron capacity 25W. Leave two seconds and more intervals, and do soldering of each terminal. Be careful because the damage of the product is often started at the time of the hand solder.

**5.Repairing**

Repair should not be done after the LEDs have been soldered. When repairing is unavoidable, a double-head soldering iron should be used (as below figure). It should be confirmed beforehand whether the characteristics of the LEDs will or will not be damaged by repairing.



**EVERLIGHT ELECTRONICS CO., LTD.**  
Office: No 25, Lane 76, Sec 3, Chung Yang Rd,  
Tucheng, Taipei 236, Taiwan, R.O.C

Tel: 886-2-2267-2000, 2267-9936  
Fax: 886-2267-6244, 2267-6189, 2267-6306  
<http://www.everlight.com>