



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDD-306-023 REV: 1.0

0.3" Dual Digit Displays

MODEL NO : ELD-306HDB/S197 ECN : Page: 1/5

■ Features :

- Industrial standard size.
- Low power consumption.
- Categorized for luminous intensity.

■ Applications:

- Audio equipment
- Instrument panels
- Digital read out display

■ Descriptions :

- The ELD-306 series is a large 7.62mm (0.3")high seven segment display design for viewing distances up to 7 meters.
- These displays provide excellent reliability in bright ambient light.
- These device is made with red segments and black surface.

PART NO	CHIP		C.C. or C.A.
	Material	Emitted Color	
ELD-306HDB/S197	GaP	Bright Red	C.A.

OFFICE : NO. 25,Lane 76,Sec.3, Chung Yang Rd., Tucheng 236, Taipei, Taiwan, R.O.C.

TEL : 886-2-2267-2000,2267-9936

FAX : 886-2-2267-6244,22676189,22676306


<http://www.everlight.com>




0.3" Dual Digit Displays

MODEL NO : ELD-306HDB/S197 ECN : _____ Page: 2/5

Package Dimensions:



- COMMON ANODE**
- 1 CATHODE C D1
 - 2 CATHODE E D1
 - 3 CATHODE D D1
 - 4 COMMON ANODE D1
 - 5 COMMON ANODE D2
 - 6 CATHODE D D2
 - 7 CATHODE E D2
 - 8 CATHODE C D2
 - 9 CATHODE G D2
 - 10 CATHODE A D2
 - 11 CATHODE F D2
 - 12 CATHODE B D2
 - 13 CATHODE B D1
 - 14 CATHODE F D1
 - 15 CATHODE A D1
 - 16 CATHODE G D1



NOTES:

1. All dimensions are in millimeters, tolerance is 0.25mm unless otherwise noted.
 2. Above specification may be changed without notice.
- Supplier will reserve authority on material change for above specification.

Device Number : DDD-306-023 REV: 1.0

0.3" Dual Digit Displays

MODEL NO : ELD-306HDB/S197 ECN : _____ Page: 3/5

■ Absolute maximum ratings at Ta = 25°C :

Parameter	Symbol	Rating	Unit
Reverse Voltage	Vr	5	V
Forward Current	If	15	mA
Operating Temperature	Topr	-40 to +85	°C
Storage Temperature	Tstg	-40 to +100	°C
Soldering Temperature	Tsol	260 ± 5	°C
Power Dissipation	Pd	45	mW
Peak Forward Current(Duty 1/10 @ 1KHZ)	If(Peak)	50	mA

■ Electronic optical characteristics :

Parameter		Symbol	MIN.	TYP.	MAX.	Unit	Condition
Luminous Intensity	Per segment	Iv	0.14	0.22	----	mcd	If=10mA
	Per decimal point		0.05	0.08	----		
Peak Wavelength		λp	----	697	----	nm	If=10mA
Dominant Wavelength		λd	----	650	----	nm	If=10mA
Spectrum Radiation Bandwidth		$\Delta \lambda$	----	90	----	nm	If=10mA
Forward Voltage		Vf	1.5	2.0	2.6	V	If=10mA
Reverse Current		Ir	----	----	10	μA	Vr=5V



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDD-306-023 REV: 1.0

0.3" Dual Digit Displays

MODEL NO : ELD-306HDB/S197 ECN : _____ Page: 4/5

■ Reliability test item and condition:

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85°C 30min ∫ 5 min L : -55°C 30min	50 CYCLE	76 PCS	0/1
3	Thermal Shock	H : +100°C 5min ∫ 10 sec L : -10°C 5min	50 CYCLE	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	If = 10 mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85°C/85% RH	1000 HRS	76 PCS	0/1



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDD-306-023 REV: 1.0

0.3" Dual Digit Displays

MODEL NO: ELD-306HDB/S197 ECN : Page: 5/5

■ Typical Electro-Optical Characteristic Curves:

