



# EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDD-511-009 REV: 1.0

0.56" Dual Digit Display

MODEL NO : ELD-511YWA ECN : \_\_\_\_\_ Page: 1/4


**Features :**

- Industrial standard size.
- Low power consumption.
- Categorized for luminous intensity.

**Description :**

- The ELD-511 series is a large 14.22mm (0.56")high seven segment display design for viewing distances up to 7 meters.
- These displays provide excellent reliability in bright ambient light.
- These device is made with white segments and gray surface.

**Package Dimension:**



**Applications:**

- Audio equipment
- Instrument panels
- Digital readout display

**NOTES:**

- 1.All dimensions are millimeters, tolerance is 0.25mm unless otherwise noted.
- 2.Above specification may be changed without notice . Supplier will reserve authority on material change for above specification.

PART NO	CHIP		C.C. or C.A.
	Material	Emitted Color	
ELD-511YWA	GaAsP/GaP	Yellow	C.C.

OFFICE : NO. 25,Lane 76,Sec.3, Chung Yang Rd., Tucheng 236, Taipei, Taiwan, R.O.C.

TEL : 886-2-2267-2000,2267-9936

FAX : 886-2-2267-6244,22676189,22676306

<http://www.everlight.com>



# EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDD-511-009 REV: 1.0

0.56" Dual Digit Display

MODEL NO : ELD-511YWA ECN :                      Page: 2/4

■ Absolute maximum ratings at Ta = 25°C :

Parameter	Symbol	Rating	Unit
Reverse Voltage	Vr	5	V
Forward Current	If	10	mA
Operating Temperature	Topr	-40 to +85	°C
Storage Temperature	Tstg	-40 to +100	°C
Soldering Temperature	Tsol	260 ± 5	°C
Power Dissipation	Pd	85	mW
Peak Forward Current(Duty 1/10 @ 1KHZ)	If(Peak)	160	mA

■ Electronic optical characteristics :

Parameter		Symbol	MIN.	TYP.	MAX.	Unit	Condition
Luminous Intensity	Per segment	Iv	0.75	1.5	----	mcd	If=10mA
	Per decimal point		0.3	0.6	----		
Peak Wavelength		$\lambda p$	----	585	----	nm	If=20mA
Dominant Wavelength		$\lambda d$	----	590	----	nm	If=20mA
Spectrum Radiation Bandwidth		$\Delta \lambda$	----	35	----	nm	If=20mA
Forward Voltage		Vf	1.7	2.0	2.6	V	If=20mA
Reverse Current		Ir	----	----	10	$\mu A$	Vr=5V



# EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDD-511-009 REV: 1.0

0.56" Dual Digit Display

MODEL NO : ELD-511YWA ECN :                      Page: 3/4

Reliability test item and condition:					
NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85°C 30min ∫ 5 min L : -55°C 30min	50 CYCLE	76 PCS	0/1
3	Thermal Shock	H : +100°C 5min ∫ 10 sec L : -10°C 5min	50 CYCLE	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	If = 20 mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85°C/85% RH	1000 HRS	76 PCS	0/1



Device Number : DDD-511-009 REV: 1.0

0.56" Dual Digit Display

MODEL NO: ELD-511YWA ECN :            Page: 4/4

