



Device Number : DDS-232-020 REV: 1.1

2.3" Single Digit Displays

MODEL NO : ELS-2326SRWA ECN : Page: 1/5

■ Features :

- Industrial standard size.
- Low power consumption.
- Categorized for luminous intensity.

■ Applications:

- Audio equipment
- Instrument panels
- Digital read out display

■ Descriptions :

- The ELS-2326 series is a large 57.0mm (2.3")high seven segment display designed for viewing distances up to 7 meters.
- These displays provide excellent reliability in bright ambient light.
- These devices are made with white segments and gray surface.

PART NO	Chip	
	Material	Emitted Color
ELS-2326SRWA	GaAlAs	Super Red

OFFICE : NO. 25,Lane 76,Sec.3, Chung Yang Rd., Tucheng 236, Taipei, Taiwan, R.O.C.

TEL : 886-2-2267-2000,2267-9936

FAX : 886-2-2267-6244,22676189,22676306

<http://www.everlight.com>


B89061564

T00332




2.3" Single Digit Displays

Package Dimensions:



- COMMON ANODE
- 1 COMMON ANODE
 - 2 CATHODE E
 - 3 CATHODE D
 - 4 CATHODE C
 - 5 COMMON ANODE
 - 6 CATHODE B
 - 7 CATHODE A
 - 8 CATHODE DP
 - 9 CATHODE F
 - 10 CATHODE G



Notes:

1.All dimensions are in millimeters , tolerance is 0.25mm unless otherwise noted.

2.Above specification may be changed without notice.

Supplier will reserve authority on material change for above specification.



2.3" Single Digit Displays

■ Absolute maximum ratings at Ta = 25°C :

Parameter	Symbol	Rating	Unit
Reverse Voltage	VR	5	V
Forward Current	IF	40	mA
Operating Temperature	Topr	-40 to +85	°C
Storage Temperature	Tstg	-40 to +100	°C
Soldering Temperature	Tsol	260 ± 5	°C
Power Dissipation	Pd	440	mW
Peak Forward Current(Duty 1/10 @ 1KHZ)	IF(Peak)	180	mA

■ Electronic optical characteristics :

Parameter		Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	Per segment	Iv	7.8	11.7	----	mcd	IF=10mA
	Per decimal point		3.2	5.0	----		
Peak Wavelength		λ p	----	660	----	nm	IF=20mA
Dominant Wavelength		λ d	----	643	----	nm	IF=20mA
Spectrum Radiation Bandwidth		Δ λ	----	20	----	nm	IF=20mA
Forward Voltage	Per segment	VF	6.0	6.8	9.6	V	IF=20mA
	Per decimal point		3.0	3.4	4.8	V	IF=20mA
Reverse Current		IR	----	----	10	μ A	VR=5V



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDS-232-020 REV: 1.1

2.3" Single Digit Displays

MODEL NO : ELS-2326SRWA ECN : Page: 4/5

■ Reliability test items and conditions:

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85°C 30min ∫ 5 min L : -55°C 30min	50 CYCLE	76 PCS	0/1
3	Thermal Shock	H : +100°C 5min ∫ 10 sec L : -10°C 5min	50 CYCLE	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	IF = 10 mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85°C/85% RH	1000 HRS	76 PCS	0/1

--	--	--	--	--	--

