



# EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDT-315-023 REV: 1.0

## 0.36" Tripple Digit Displays

MODEL NO : ELT-315SURWA/S530-A2 ECN : \_\_\_\_\_ Page: 1/5

### ■ Features :

- Industrial standard size.
- Low power consumption.
- Categorized for luminous intensity.

### ■ Applications:

- Audio equipment
- Instrument panels
- Digital readout display

### ■ Description :

- The ELT-315 series is a large 9.2mm (0.36")high seven segment display design for viewing distances up to 7 meters.
- These displays provide excellent reliability in bright ambient light.
- These device is made with white segments and gray surface.

PART NO	CHIP		C.C. or C.A.
	Material	Emitted Color	
ELT-315SURWA/S530-A2	AlGaInP	Hyper Red	C.C.

OFFICE : NO. 25,Lane 76,Sec.3, Chung Yang Rd., Tucheng 236, Taipei, Taiwan, R.O.C.

TEL : 886-2-2267-2000,2267-9936


FAX : 886-2-2267-6244,22676189,22676306

<http://www.everlight.com>





## 0.36" Tripple Digit Displays

### Package Dimension:



- COMMON CATHODE*
- 1 ANODE E
  - 2 ANODE D
  - 3 ANODE DP
  - 4 ANODE C
  - 5 ANODE G
  - 6 NP
  - 7 ANODE B
  - 8 COMMON CATHODE DIG.3
  - 9 COMMON CATHODE DIG.2
  - 10 ANODE F
  - 11 ANODE A
  - 12 COMMON CATHODE DIG.1



### NOTES:

1. All dimensions are millimeters, tolerance is 0.25mm unless otherwise noted.
  2. Above specification may be changed without notice.
- Supplier will reserve authority on material change for above specification.



## 0.36" Tripple Digit Displays

### ■ Absolute maximum ratings at Ta = 25°C :

Parameter	Symbol	Rating	Unit
Reverse Voltage	Vr	5	V
Forward Current	If	25	mA
Operating Temperature	Topr	-40 to +85	°C
Storage Temperature	Tstg	-40 to +100	°C
Soldering Temperature	Tsol	260 ± 5	°C
Electrostatic Discharge	ESD	2000	V
Power Dissipation	Pd	60	mW
Peak Forward Current(Duty 1/10 @ 1KHZ)	If(Peak)	160	mA

### ■ Electronic optical characteristics :

Parameter		Symbol	MIN.	TYP.	MAX.	Unit	Condition
Luminous	Per segment	Iv	0.45	1.3	----	mcd	If=2mA
	Intensity		Per decimal point	2.8	8.5	----	mcd
				0.11	0.75	----	mcd
				1.05	4.00	----	mcd
Peak Wavelength		$\lambda p$	----	632	----	nm	If=20mA
Dominant Wavelength		$\lambda d$	----	624	----	nm	If=20mA
Spectrum Radiation Bandwidth		$\Delta \lambda$	----	20	----	nm	If=20mA
Forward Voltage		Vf	----	2.0	2.4	V	If=20mA
Reverse Current		Ir	----	----	10	$\mu A$	Vr=5V



# EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDT-315-023REV: 1.0

0.36" Tripple Digit Displays

MODEL NO : ELT-315SURWA/S530-A2 ECN : \_\_\_\_\_Page: 4/5**Reliability test item and condition:**

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85°C 30min ∫ 5 min L : -55°C 30min	50 CYCLE	76 PCS	0/1
3	Thermal Shock	H : +100°C 5min ∫ 10 sec L : -10°C 5min	50 CYCLE	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	If = 10 mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85°C/85% RH	1000 HRS	76 PCS	0/1



# EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DDT-315-023 REV: 1.0

0.36" Tripple Digit Displays

MODEL NO: ELT-315SURWA/S530-A2 ECN : \_\_\_\_\_ Page: 5/5

## Typical Electro-Optical Characteristic Curves:

